

J7F2EDEN12G



Processor	VIA Eden Prozessor 1,2 GHz, FSB 133 MHZ 6W Fanless
Chipset	VIA CN700
Graphic	Integrated S3 UniChrom Pro
Memory	1x DDR II 400/533 DIMM up to 1 GB
Audio	AC'97 6-CH Codec
Storage	4 ATA-133, 2 SATA, RAID
LAN	10/100 LAN on Board
On board I/O	8 USB 2.0 2x COM Port (one at Rear port, one by header)
Expansion	PCI Slot
AD-Connector	für Adapter-Boards (See Adapter-Boards)
Dimension	Mini ITX form factor (17 x 17 cm)

Adapter-Boards (Optional)	
Art.-Nr. 32561 - JAD2COM	2x COM Port
Art.-Nr. 32562 - JAD4COM	4x COM Port
Art.-Nr. 32559 - JAD3RTLANS	3x Giga Lan
Art.-Nr. 32560 - JAD3RTLANS	3x Lan 10/100
Art.-Nr. 32557 - JAD1RTLANS	1x Giga Lan
Art.-Nr. 32558 - JAD1RTLANS	1x Lan 10/100
Art.-Nr. 32564 - JADPCM	Card Bus Type I + II, with CF card Reader
Art.-Nr. 32596 - JAD12VB	12 V Mini-ITX Power supply
Art.-Nr. 32563 - JAD7LVCOM	LVDS Controller + 2x COM Port
Art.-Nr. 32565 - AD7DLV	LVDS + DVI connector

Zubehör



Treiber- und Manual-CD



HDD-Kabel



SATA-Kabel



Com Port Slot